


MODELS 4090HK17 / 4090HK17/20

5.5 HP SINGLE STAGE TWO CYLINDER PORTABLE GAS COMPRESSORS



MODEL 4090HK17



MODEL 4090HK17/20

ROLAIR STANDARD FEATURES

- | | |
|--|---|
| <p>PUMP: ROLAIR Quality, Heavy-Duty, Single Stage, Ball Bearings, Cast-Iron Twin Cylinders, Hardened Steel Valve Plates with Swedish Lamellar Reed Valves, Aluminum Alloy Connecting Rods with Automotive-Style Inserts, Multi-Finned 11" Flywheel, Oil Sight Gauge and Splash Lubrication.</p> <p>ENGINE: 5.5 HP Honda 4 Cycle, Complete Die Cast Aluminum Alloy with Cast-Iron Sleeve, Overhead Valves, Retractable Starter, On/Off Switch, Splash Lubricated, Low Oil Shutdown</p> <p>TANK ASSEMBLY: Non-Code, 9 Gallons (optional 20 Gallon Tank)</p> <p>WHEELS: One 410/350 x 4 2-Ply Fully-Pneumatic <i>with Sealant</i> (4090HK17/20 uses two wheels)</p> | <p>PERFORMANCE @ 100 PSI:
Cu. Ft. Displaced - 13.1
Cu. Ft. Free Air - 8.9</p> <p>DIMENSIONS:
L46" x W19" x H28" - 4090HK17
L47" x W22" x H34" - 4090HK17/20</p> <p>APPROXIMATE SHIPPING WEIGHT:
174 lbs.—4090HK17
198 lbs.—4090HK17/20</p> |
|--|---|

STANDARD EQUIPMENT

- | | |
|---|---|
| <ul style="list-style-type: none"> • Automatic Pilot Valve Operation • Industrial Flexible Discharge Hose • Automatic Idle Control for Economy and Long Service Life • 110/135 PSI Operating Pressure • Air-Cooled Aftercooler | <ul style="list-style-type: none"> • Pressure Gauge 0-200 in 5 lb. Graduations • Intake Filter with Silencer and Replaceable Element • Schmidt Belt Tightening Device • Safety Relief Valve • Totally Enclosed Steel Belt Guard • Accessory Support Bracket |
|---|---|

OPTIONAL EQUIPMENT

Filter-Regulator-Lubricator Sets, Robin Engines

ROLAIR SYSTEMS

606 S. LAKE ST, P O BOX 346, HUSTISFORD WI 53034-0346
SALES FAX: 920.349.3691 - SERVICE FAX: 920.349.8861
PHONE: 920-349-3281

www.rolair.com

